



575000A~~XO~~ E9J804

E9J804	E9J804	
515000 daN*m	3725715 Lb*ft	Momento statico massimo al perno torretta • Max. static moment at the turret pin Moment statique max. a l'axe de la tourelle • Max. statisches ubmoment am kransaulenbolzen
57.84 m	189' 9"	Sbraccio idraulico • Hydraulic boom length Longueur du bras hydraulique • Hydraulic reichweite
		Sbraccio con prolunghe manuali • Boom length with manual extensions Longueur du bras avec rallonges manuelles
33270 daN*m	240688 Lb*ft	Coppia di rotazione • Slew torque • Moment de rotation • Drehmoment
73 s 360°	73 s 360°	Tempo di rotazione • Slewing speed • Temp de rotation • Schwenkgeschwindigkeit
3150+3150 mm 5200+5200 mm	10' 4" + 10' 4" 17' 1" + 17' 1"	Uscita stabilizzatori • Outriggers extensions Sortie des bequilles • Breite der abstützung
12340 mm	40' 6"	Larghezza stabilizzatori • Outriggers width Largeur des bequilles • Breite der abstützung
10530 mm	34' 7"	Lunghezza • Length • Longeur • Länge
2548 mm	8' 4"	Larghezza • Width • Largeur • Breite
2880 mm	9' 5"	Altezza • Height • Huteur • Höhe
50450 kg	111223 lbs	Peso (senza olio e montaggio) • Weight (without oil and fitting) Poids (sans huile et montage) • Gewicht (ohne öl und ohne)
120+110 l/min	31+29 us gal/min	Portata pompa (*) • Pump delivery (*) • Capacité de la pompe (*) • Pumpenleistung (*)
330 bar	4692 psi	Pressione • Pressure • Pression • Druck
1250 l	330 us gal	Capacità serbatoio olio • Oil tank capacity • Capacité de reservoir d'huile • Öl tank inhalt

STANDARD



OPTIONAL



(*) Consigliata, (*) Recommended, (*) Recommande, (*) Empfohlen.